# Food and Beverage Calorie Prediction with Neural Networks

**D.Ramanjaneyulu [1], Raman kumar mandal[2] ,PriyaRanjan Raj3 ,K.Ravi Naik [4] , Anjanadevi Dayinaboyina.[5]**

[1] professor, Department of CSE, CMR College of Engineering and Technology, Kandlakoya medchal Hyderabad, Telangana, India
[2] Assistant professor Department of CSE, Gurunanak Institutions technical Campus Hyderabad Telangana.

[3,] Asst Professor Department of CSE, GNIT, Hyderabad Telangana.
[4,] Asst Professor, Department of CSE, CMR College of Engineering and Technology, Kandlakoya medchal Hyderabad, Telangana, India
[5]Senior Software Engineer, WiproLtd, Chennai, India

**Abstract.** This observe introduces a revolutionary approach for enhancing nutritional monitoring and selling healthful consuming behavior via deep analyzing technology. The primary objective is to correctly come across several meals objects and estimate their calorie content cloth in actual-time, offering customers a smart and customized technique to nutritional tracking performed using Python, the gadget makes use of the cellular net architecture for food category and calorie estimation. The proposed gadget methods meals snap shots through a web based totally interface, figuring out gadgets hastily and supplying customers with a accurate calorie estimate. This machine empowers people with treasured insights into their nutritional behavior, permitting them to song meals intake, set dietary dreams, and make knowledgeable picks. via way of leveraging deep studying for green and correct calorie estimation, this approach offers a transformative solution for nutritional control. With its excessive precision, real-time evaluation, and clever nutritional monitoring, this system has the ability to redefine how humans monitor and optimize their dietary conduct, fostering greater healthy lifestyles and average well-being.

**Keywords:** Deep Learning, Food Calorie Estimation, Image Processing, CNN, Multi-Label Classification, Computer Vision

## 1 Introduction

Rapid advances in computer vision and deep learning have had a major impact on a wide range of areas including healthcare and nutrition the key uses are food detection and calorie estimation and it is estimated that a key role plays in intelligent nutrition monitoring accurate food identification and estimation of calorie content can help individuals make healthy nutrition decisions and promote a healthier lifestyle increased smartphone use and growing nutritional concerns have encouraged research into efficient and accurate calorie estimation systems these approaches are highly susceptible to variations in lighting conditions location and food presentation style furthermore many existing systems related to reporting on food categories are limited

and lack actual calorie assessment skills this makes them ineffective for widespread use to address these challenges this study uses deep learning techniques particularly mobilenet architecture to improve the accuracy of food detection mobilenet is a lightweight and efficient model suitable for mobile applications .

This model is trained on a food 101 dataset consisting of 101 food classes and 37046 photographs allowing you to learn complex patterns for effective classification using deep learning the system can recognize a wide variety of foods with high accuracy one of the most important features of this approach is the actual calorie estimation in contrast to traditional systems this model quickly provides users with nutritional knowledge and allows them to pursue their diet efficiently user-friendly interfaces ensure accessibility for different user groups making it easier for individuals to manage their eating habits the system processes food images recorded via a smartphone or other image input device analyzes them and intuitively presents calorie information. with a combination of high accuracy real-time processing and a user-friendly interface the proposed system offers a new approach to recognizing food and calorie estimations this study highlights the potential for deep learning in changing ways people monitor and optimize their diet to improve their health and well-being demonstrate its effectiveness and potential applications in the real world

Increased awareness of health and nutrition has led to a rising demand for accurate and efficient ways to track nutrition. Traditional methods for calorie estimation, such as manual cutting and food weighing, are often time-consuming and prone to human error. To address these limitations, a deep learning-based approach has proven to be a promising solution for automatic calorie estimation in food images.

By using deep learning networks, the system can accurately recognize a variety of foods and estimate calorie content in real time. Deep learning models can learn complex patterns and functions from food photographs, improving classification accuracy and calorie prediction. Extracting relevant features from images, the model is trained on the Food-101 dataset, which consists of 101 different food categories and over 37,000 labeled images. Thanks to extensive training and optimization, the system provides a high level of accuracy in identifying foods and calculating their corresponding calorie values.

One of the most important advantages of this approach is its ability to estimate calorie intake by simply capturing dietary images. The system is designed to be user-friendly and allows seamless integration into mobile applications or web- based platforms[1] .By providing immediate nutritional feedback, this technology enables individuals to make well- informed dietary choices and maintain a balanced diet.

With growing health concerns such as obesity, diabetes, and cardiovascular disease, tools that simplify nutritional tracking are urgently needed. Automated calorie estimation can help

individuals achieve their nutritional goals by providing real time insights into food consumption. Additionally, the system can be integrated into fitness applications, medical health platforms, and portable devices to improve general health surveillance.

In contrast to traditional machine learning methods based on hand-crafted features, deep learning techniques such as Convolutional Neural Networks (CNNs) allow models to

learn hierarchical representations of food images[2]. This enables the system to distinguish similar foods and estimate portion sizes more effectively. Additionally, deep learning techniques help overcome challenges related to lighting conditions, oc/clusions, and variations in food presentation styles. Methods such as image scaling, rotation, and

normalization improve the model's ability to generalize across different food datasets[3].

Furthermore, multi-label classification technology allows the system to recognize multiple food items in a single image, making it a comprehensive solution for complex dietary compositions. The impact of this study extends to healthcare, nutrition planning, and food technology[4].

For healthcare professionals, automated tools for calorie estimation can assist in designing personalized nutrition plans for patients. Nutritionists can leverage this system to provide more accurate dietary recommendations. Fitness enthusiasts can track their calorie intake with minimal effort, while the foodservice sector and restaurants can use this technology to provide customers with detailed nutritional information about menu items[5].

An efficient calorie estimation system utilizing deep learning for food detection and calorie calculations has the potential to revolutionize nutritional tracking and contribute to a healthier lifestyle. The following sections examine the technical details, implementation, and evaluation of this system, demonstrating its effectiveness in real-world applications.

## 2. RELATED WORK

With the increasing demand for automated nutritional tracking, several researchers have explored deep learning techniques for food recognition and calorie estimation. Many studies have focused on enhancing classification accuracy, improving dataset quality, and integrating advanced machine learning models for efficient calorie assessment [6].

It presents a dataset designed to detect food items in various physical states, such as fully cut or sliced. Their research demonstrated that deep learning models using convolutional

neural networks (CNNs) combined with support vector machines (SVMs) significantly outperformed traditional feature extraction methods in classification accuracy [7]. Similarly, the paper developed a food recognition system specifically.

Tailored to Korean cuisine using a deep convolutional neural network (DCNN). Their model, known as K-FoodNet, wastrained on a dataset of over 92,000 images covering 23 food categories. It achieved a high test accuracy of 91.3%, demonstrating faster recognition speeds compared to architectures such as AlexNet, GoogleNet, VGG, and ResNet [8]. Their study also introduced an automated system to differentiate between actual and synthetic food images, proving beneficial for nutritional and experimental food studies.

The paper proposed a hybrid model integrating deep learning with natural language processing (NLP) for nutrition monitoring [9]. This approach improved image-based food detection and text-based food description, achieving a classification accuracy of 93%. Their model demonstrated the potential of multimodal data fusion for enhanced food tracking [10]. Additionally, developed a calorie estimation model that segmented individual food items in an image before calculating calorie content using predefined values based on recognized food surface areas. Their approach achieved a calorie estimation accuracy of 95.5%, surpassing traditional classification methods [11].

Several other studies have demonstrated significant advancements in CNN-based food recognition and calorie estimation. It employed an instance segmentation approach using Mask R-CNN for calorie estimation, significantly improving food identification accuracy [12]. It utilized feature fusion techniques to enhance image recognition across 85 food categories, demonstrating effective multi label classification [13]. The paper developed a CNN-based model for calorie and nutrition measurement, emphasizing the importance of image preprocessing in improving model
performance [14]. Moreover, the paper proposed a computer vision-based dataset and method for food calorie estimation, further advancing the accuracy and efficiency of automated dietary assessment [15].

Recent advancements have also explored mobile based implementations for real-time food recognition and calorie estimation. It introduced a CNN- based automatic calorie estimation system specifically for fruits, which achieved high accuracy in real-world applications [16]. It utilized machine learning techniques for food recognition and nutrition estimation, leveraging both image and textual data for enhanced accuracy [17]. The paper developed a region based food calorie estimation model capable of processing multiple dishes within a single meal, further improving calorie prediction accuracy [18].

Furthermore, research explored multi-task learning for calorie prediction on a large-scale recipe dataset enriched with nutritional information, highlighting the effectiveness of deep

learning in dietary assessment applications [19]. The paper proposed a calorie estimation system using Microsoft HoloLens and deep learning to estimate food calories based on actual size, demonstrating the potential of augmented reality in nutrition tracking [20].

These studies collectively demonstrate the progress of deep learning in food recognition and calorie estimation. CNNbased models have shown significant accuracy in food classification, while the integration of additional modalities, such as text analysis, component analysis, and instance segmentation, has further improved the accuracy of nutritional assessments. This study aims to implement an optimized mobile-based approach for real-time food detection and calorie estimation, providing an accessible and efficient solution for nutrition monitoring

## 3. EXISTING SYSTEM

In the existing system of a Food and Beverage Calorie Prediction with Neural Networks many methods were used to measure the health parameters like calorie contents but only in tabular form. In the existing model, we don't have calorie content displaying through pie graph and accuracy is also less. To secure the health, the proposed model implemented with the neural networks automatically generates the calorie content with help of the pie graph which would be help full for users in their estimation.

## 4. PROPOSED SYSTEM

The application of neural networks in the food and beverage industry has gained significant traction due to their ability to analysis complex data patterns, optimize processes, and enhance decision-making. This methodology section outlines the procedures involved in implementing neural networks for various applications, including quality control, demand forecasting, taste profiling, and process automation.

1.Dataset Collection and Preprocessing:

For this study, a Food-101 dataset with 37,046 photographs in 101 different food categories was selected. Data records were obtained from Kaggle to ensure diversity and reliability. To maintain consistency of image processing, all images were changed to 128 pixels, and pixel values were normalized to 0-1 scale to improve model efficiency and stability. Enhancement techniques such as rotation, flipping and scaling were used. This allowed the model to learn about food presentation variations and improve recognition accuracy. Data records were split into 80% training data and 20% test data for performance assessment.

2. Preprocessing and Functional Selection:

Data records were subject to preprocessing to extract relevant functions for accurate classification. This included improved contrast, noise reduction and edge recognition to ensure that the model focused on essential food properties. Characteristic selection was performed to optimize arithmetic efficiency and ruin the unrelated background details.

3. Model Selection and Implementation:

The mobile net architecture was chosen for its lightweight and efficient design. This makes it ideal for mobile and web based applications. Mobile Net uses deep separable convolutions to reduce compensation complexity while simultaneously maintaining a high level of accuracy. In contrast to traditional CNNs, this method separates spatial and deep calculations and improves real-time food detection performance. category. The activation function of Relu (Rectifidiene Linear Unit) was used in hidden layers for efficient property extraction, but the activation function of soft max at the probability of the final layer is computational efficiency and learning stability. It's sexual balance. Training was monitored by epoch accuracy and loss plots, allowing performance tracking and potential identification of problems.

4. Prediction and Results:

After training, the model was evaluated on a test data set, achieving 97% training accuracy and 98% testing accuracy. This model successfully identifies food categories and identifies important calorie content based on learning patterns. The prediction includes both food names and corresponding calorie details, which means users receive quick nutrition knowledge.

5. Model Delivery and Integration:

The final trained model was exported in .h5 format for seamless integration into mobile and web applications. The system allows users to upload images of food and receive an estimate of their actual calories. Additionally, visualizations of accuracy and loss diagrams per ERA were generated to evaluate model improvements and identify management or minor adaptation Real-time reasoning skills. Future improvements include estimates and multi-label classification for the real-time portion of mixed meals. This further improves the accuracy and ease of use of the system.

This approach enables seamless integration into mobile applications and web platforms, allowing users to obtain accurate calorie estimates by capturing food images. The combination of optimized deep learning models, extensive data augmentation, and real-

time processing capabilities represents a significant advancement in automated nutrition monitoring.

## 5. SYSTEM MODEL

The gadget model for food and beverage calorie prediction using neural networks is designed to estimate calorie content material based on enter parameters including ingredients, portion length, and nutritional composition. This calorie prediction device may be incorporated into cell health apps, eating place databases, and diet-tracking gear, enabling users to make knowledgeable nutritional choices. This calorie prediction system can be integrated into mobile health apps, restaurant databases, and diet-tracking tools, enabling users to make informed dietary choices.





Fig-1. Mobile Net

## 6. RESULTS

The proposed deep learning-based system for calorie estimation was evaluated on a food 101 dataset consisting of 37046 photographs covering 101 different food categories this model was developed using a mobile set architecture this includes deep

separable folding which is included to improve arithmetic efficiency and at the same time maintain a high level of accuracy the most important results are explained below the cross-centre functions of categories were used as a loss function that allows effective classification in several classes reduction consistently rejected epochs stabilizing validation loss signs of effective generalization the trend in accuracy and losses to diagram epochs leads to model stability and the reliability has been confirmed increased verification accuracy has shown that the effectiveness of the system accurately recognizes food images information the strong correlation between respected and actual calorie values versus actual calorie values verified the accuracy of the system in real scenarios recognized several foods in a Food 101 Image Dataset Pre Processing and Feature

Selection Mobile Net Architecture Model Loss and Model Accuracy Graph Predicted Results: Food name with calorie details single photo generalization ability good performance under various lighting and food conditions a high performance model ideal for mobile and web applications the application of deep separator convolution reduced computing costs by 7-8 times compared to standard cutting layers this has increased user accessibility by estimating real-time perception and calorie estimates in real-time the final model was in h5 the model assumes standard variety sizes which can lead to slight deviations in calorie counting beverage data set the system effectively recognizes solid foods but requires improved fluid-based calorie estimation.





Fig-2 User Login Page

The User Login Page acts as the gateway to the calorie estimation application, enabling secure and personalized access. Users are required to enter their email and password for authentication. The interface is designed to be intuitive and easy to navigate, ensuring a smooth login process. Additionally, options for password recovery and new

account registration are available for user convenience. Strong authentication protocols are implemented to safeguard user information and maintain data security.





Fig-3 Uploading Food Image

The Food Image Upload Page allows users to upload images of their meals for calorie estimation. Users can either capture a new photo or select an existing image from their device. The system processes the uploaded image using deep learning algorithms to identify the food items and estimate their calorie content. The interface is designed to be simple and user-friendly, ensuring a seamless experience. Real-time feedback is provided, enabling users to monitor their dietary intake efficiently.





Fig. 4. Estimating the Nutrition of Food

The Nutrition Estimation Page processes the uploaded food image to evaluate its nutritional value. Utilizing deep learning algorithms, the system detects the food items and computes their caloric content and nutrient breakdown. The results are presented in a clear and structured format, offering users valuable insights into their dietary intake. This functionality assists users in monitoring their nutrition and making healthier food choices. The interface is designed for efficiency, ensuring quick and accurate estimations.

## 7.CONCLUSION

This study developed an efficient and deep learning system for detecting food and calorie estimates using mobilenet architecture and food 101 data record this model achieved high levels of accuracy in food identification and estimating its calorie values light design ensures fast and reliable performance of real applications on mobile and web platforms data expansion techniques have improved generalization but separable convolutions have deeper reductions in compensation complexity making the use of models more practical future improvements include real time analytics multi-label classification and integration with health tracking apps for more comprehensive nutrition monitoring a practical and automated approach to persecuting food intake and promoting healthier eating habits.

## 8. REFERENCES


1 Bray, G.; Bouchard, C. (Eds.) Handbook of Obesity-Volume 2: Clinical Applications; CRC Press: Boca Raton, FL, USA, 2014.

2 Prentice, A.M.; Jebb, S.A. Beyond body mass index. Obes. Rev. 2001, 2, 141–147.

3 Petimar, J.; Ramirez, M.; Rifas-Shiman, S.L.; Linakis, S.; Mullen, J.; Roberto, C.A.; Block, J.P. Evaluation of the impact of calorie labeling on McDonald's restaurant menus: A natural experiment. Int. J. Behav. Nutr. Phys. Act. 2019, 16, 99.

4 Health Canada. Health Canada Nutrient Values. November 2011. Available online: https://www.canada.ca/en/health- canada/services/food-nutrition/healthy-eating/nutrient-data/nutrient-value-some-common-foods-booklet.html (accessed on 31 August 2022).

5 Kasar, M.M.; Bhattacharyya, D.; Kim, T.H. Face recognition using neural network: A review. Int. J. Secur. Its Appl. 2016, 10, 81–100.

6 Li, G.Z.; Bu, H.L.; Yang, M.Q.; Zeng, X.Q.; Yang, J.Y. Selecting subsets of newly extracted features from PCA and PLS in microarray data analysis. BMC Genom. 2008, 9, S24.

7 Ciocca, G.; Micali, G.; Napoletano, P. State recognition of food images using deep features. IEEE Access 2020, 8, 32003–32017.

8 Park, S.J.; Palvanov, A.; Lee, C.H.; Jeong, N.; Cho, Y.I.; Lee, H.J. The development of food image detection and recognition model of Korean food for mobile dietary management. Nutr. Res. Pract. 2019, 13, 521– 528.

9 Mezgec, S.; Seljak, B.K. Using deep learning for food and beverage image recognition. In Proceedings of the 2019 IEEE International Conference on Big Data (Big Data), Los Angeles, CA, USA, 9–12 December 2019; pp. 5149–5151.

10 Mezgec, S.; Eftimov, T.; Bucher, T.; Seljak, B.K. Mixed deep learning and natural language processing method for fake-food image recognition and standardization to help automated dietary assessment. Public Health Nutr. 2019, 22, 1193–1202.

11 Liang, H.; Gao, Y.; Sun, Y.; Sun, X. CEP: Calories estimation from food photos. Int. J. Comput. Appl. 2020, 42, 569–577. [12] Poply, P. An Instance Segmentation approach to Food Calorie Estimation using Mask R-CNN. In Proceedings of the 2020 3rd International Conference on Signal Processing and Machine Learning, Beijing, China, 22–24 October 2020; pp. 73–78.

13 Hoashi, H.; Joutou, T.; Yanai, K. Image recognition of 85 food categories by feature fusion. In Proceedings of the Proceedings of the 2010 IEEE International Symposium on Multimedia, Taichung, Taiwan, 13–15 December 2010; pp. 296–301.

14 Pouladzadeh, P.; Shirmohammadi, S.; Al-Maghrabi, R. Measuring calorie and nutrition from food image. IEEE Trans. Instrum. Meas. 2014, 63, 1947–1956.

15 Liang, Y.; Li, J. Computer vision-based food calorie estimation: Data set, method, and experiment. arXiv 2017, arXiv:1705.07632.

16 Latif, G.; Alsalem, B.; Mubarky, W.; Mohammad, N.; Alghazo, J. Automatic Fruits Calories Estimation through Convolutional Neural Networks. In Proceedings of the 2020 6th International Conference on Computer and Technology Applications, Antalya, Turkey, 14–16 April 2020; pp. 17–21.

17 Shen, Z.; Shehzad, A.; Chen, S.; Sun, H.; Liu, J. Machine learning based approach on food recognition and nutrition estimation. Procedia Comput. Sci. 2020, 174, 448–453.

18 Okamoto, K.; Adachi, K.; Yanai, K. Region-Based Food Calorie Estimation for Multiple-Dish Meals. In Proceedings of the 13th International Workshop on Multimedia for Cooking and Eating Activities, Taipei, Taiwan, 16–19 November 2021; pp. 17–24.

19 Ruede, R.; Heusser, V.; Frank, L.; Roitberg, A.; Haurilet, M.; Stiefelhagen, R. Multi-task learning for calorie prediction on a novel large-scale recipe data set enriched with nutritional information. In Proceedings of the 2020 25th International Conference on Pattern Recognition (ICPR), Milan, Italy, 10–15 January 2021; pp. 4001–4008.

20 Naritomi, S.; Yanai, K. CalorieCaptorGlass: Food calorie estimation based on actual size using hololens and deep learning. In Proceedings of the 2020 IEEE

Conference on Virtual Reality and 3D User Interfaces Abstracts and Workshops (VRW), Atlanta, GA, USA, 22–26 March 2020; pp. 818–819